Screen Protection Sheet Attachment Instructions

Thank you for purchasing the Screen Protection Sheet (5 sheets per set). Please read the following instructions prior to attaching this sheet to the screen.



• In operating environments with high levels of humidity and moisture, condensation or mist may form between the sheet and the unit's screen.

- *Important* This sheet is made from flexible polyester, and is not designed to protect against sharp or hard objects. (i.e. it may tear if struck by a sharp object)
 - If the sheet should start to peel away from the screen, DO NOT use a sharp or hard object (i.e. a knife, or pin) to remove the sheet, since it could scratch or damage the screen.
 - This sheet is designed specifically to protect the screen from moisture, liquids and dirt.
 - This sheet's matte finish helps to reduce glare and Newton rings (screen curve reflection lines).
 - This sheet does not interfere in any way with the Touch Panel's normal touch operation.
 - When dirt and smudges on the sheet begin to reduce the screen's visibility, please replace the sheet with a new one.

■ To Attach the Sheet

- 1. Prior to attaching the sheet, please clean the screen thoroughly with a soft cloth. (Use either water or a neutral detergent to remove tougher stains)
- 2. Remove the sheet's Protective Film, and peel off the Backing Sheet slightly to expose the Protection Sheet's adhesive surface. (*1)
- 3. Starting at the top of the screen, slowly attach the Protection Sheet while peeling off the Backing Sheet.



(*1) Be sure completely to peel off the Protection Sheet's Protective Film.

Protection Sheet Specifications/Characteristics

| Sheet Material | | Polyester Film |
|---------------------------------|------------------|--|
| Chemical Resistance Level | Protects Against | Hexane, Kerosene, Engine Oil, Diesel Oil, Lubrication Oil, |
| | | Glycerine, Acetone, Acetic Anhydride, Benzene Ammonia, Sulfur Dioxide, Potassium Hydroxide, |
| | | Caustic Soda, Nitrobenzene |